

PRODUCT ANNOUNCEMENT



Stainless Steel - Vertical Windlass

3500W / 4000W / Hydraulic





Main features

- Luxury stainless steel base and drum
- Independent gypsy and drum operation
- Chain counter magnet pre-installed as standard
- Anodised gearbox suitable for marine use
- Available DC, AC and hydraulic motors
- Chain pipe included in the package
- Manual chain release

Construction Motor size			316 L Stainless Steel			
			3500 W	4000 W	Hydraulic - 8cc	
Power Supply (V)			24	230-400	•	
Maximum Pull (kg)			3000	3100	3700	
Working Load (kg)			800	840	1000	
Amps at Working Load (A)			240	16 - 9	0 0 -0 0	
Line Speed at Working Load (m/min)			7	8	10	
Max. Line Speed (m/min)			9	10	10	
Net Weight with Drum (kg)			160	160	145	
Max. Hydraulic Pressure (bar)				-	200	
Max. Hydraulic Flow (lt/min)			-	-	28	
Circuit Breaker (available separately)			636601	Included in the switchboard		
Control Box / Switchboard			Included in the package	Available separately	-	
SX7	CHAIN	Type**	Code	Code	Code	
	12 mm. ISO 4565					

SX7	CHAIN	Type**	Code	Code	Code
With Drum	12 mm, ISO 4565 / 13mm, DIN 766	cw	636459	636520	636526
	14 mm	cw	636518	636522	636524
	12 mm, ISO 4565 / 13mm, DIN 766	ccw	636464	636521	636527
	14 mm	ccw	636519	636523	636525

^{*} Non-standard configuration. Optional gypsies can be supplied separately.





^{**}cw: the windlass pulls clockwise ccw: the windlass pulls counter clockwise