

NEW PRODUCT ANNOUNCEMENT

X1 Dark Vertical Windlass

500W / 800W / 1000W







Main features

- ✓ Independent gypsy and drum operation

- Chain & rope management by the spring loaded arm
- Ohain counter magnet pre-installed as standard
- ✓ Marine anodised aluminium gearbox



X2 Dark

Vertical Windlass

1000W





- Special watertight stainless steel ball bearing in the base
- Manual override available







Construction		Dark Versio	n
Motor Size	500 W	800 W	1000 W
Power Supply (V)	12	12	12
Maximum Pull (kg)	630	700	900
Working Load (kg)	95	100	125
Amps at Working Load (A)	60	110	125
Line Speed at Working Load (m/min)	23	25	18
Max. Line Speed (m/min)	26	28	30
Net Weight Low Profile (kg)	11	13	16
Net Weight with Drum (kg)	12	14	17


X1	Chain	Rope	Code	Code	Code
With Drum	8 mm, ISO 4565 / DIN 766	12 mm, 3-strand	*	636702	*
Low	6 mm, ISO 4565 / DIN 766	10-12 mm, 3-strand	636206	636433	*
Profile	8 mm, ISO 4565 / DIN 766	12 mm, 3-strand	636700	636432	636701

Product codes with * are available upon request.

Construction			Dark Version	
Motor Siz	e		1000 W	
Power Su	pply (V)		12	
Maximum	Pull (kg)		1000	
Working I	Load (kg)		150	
Amps at \	Working Load (A)		117	
Line Spee	ed at Working Loa	ad (m/min)	20	
Max. Line	Speed (m/min)		40	
Net Weigl	ht Low Profile (kg		19	
Net Weigl	ht with Drum (kg)		20	
X2	Chain	Rope	Code	
	8 mm,	14 mm 2 strand	626704	

	X2	Chain	Rope	Code
	With	8 mm, ISO 4565 / DIN 766	14 mm, 3-strand	636704
	Drum	10 mm, DIN 766	-	636708
		10 mm, ISO 4565	-	636706
	Low Profile	8 mm, ISO 4565 / DIN 766	14 mm, 3-strand	636703
		10 mm, DIN 766	-	636707
		10 mm, ISO 4565	-	636705

Installation positions



Lofrans' designed marine anodised aluminium gearbox

Low Profile

