

## HAND HELD REMOTE CONTROLS FOR WINDLASS

### THETIS 1002

HAND HELD REMOTE CONTROL



Cradle

- ✓ Elegant and functional design
- ✓ Soft rubber casing that allows for anti-slip grip
- ✓ IP66-rated with waterproof plug & socket IP67-rated
- ✓ Flexible cable extensible up to 4 metres (approximately) for maximum freedom on board during anchoring manoeuvring
- ✓ With reinforced covers & buttons
- ✓ Inversion polarity protection
- ✓ Parallel connection
- ✓ 2 buttons (up-down)
- ✓ Support bracket for stowing



### THETIS 5003

HAND HELD REMOTE CONTROL  
CHAIN COUNTER



Cradle

- ✓ Specially designed to provide full control in anchoring
- ✓ Soft rubber casing that allows for anti-slip grip
- ✓ IP66-rated with waterproof plug & socket IP67-rated
- ✓ Flexible cable extensible up to 4 metres (approximately) for maximum freedom on board during anchoring manoeuvring
- ✓ Advanced microprocessor that offers a series of advantages for full anchoring control
- ✓ With reinforced covers & buttons
- ✓ Chain speed indicator / mooring length in meters or feet
- ✓ Voltage indicator
- ✓ Up alarm sensor
- ✓ Key tones adjustment
- ✓ High vision LCD display / Backlit display screen / Eight level of contrast
- ✓ Six language menu (IT, EN, FR, DE, ES, GR)
- ✓ Able to control free fall windlasses
- ✓ Parallel connection
- ✓ Support bracket for stowing

Code	73631
Command Transmission	Wire
Number of Buttons	2
Voltage (V DC)	12 - 24
Operating Temperature (°C)	From -10 to +60
Protection Rating*	IP66
Max. Contacts Amperage (A)	2
Weight (g)	340
Dimensions (mm)	155 x 65 x 45

\* When installed

Code	73632
Command Transmission	Wire
Number of Buttons	3
Voltage (V DC)	12 - 24
Operating Temperature (°C)	From -10 to +60
Protection Rating*	IP66
Max. Contacts Amperage (A)	2
Weight (g)	410
Dimensions (mm)	155 x 65 x 45

\* When installed

# THETIS 7003

## RADIO CONTROL CHAIN COUNTER



**2**  
Years Limited  
Warranty



Cradle



- ✓ Without cable ties, plug or panels & with rechargeable battery
- ✓ With reinforced covers & buttons
- ✓ Chain speed indicator / mooring length in meters or feet
- ✓ Voltage indicator
- ✓ Up alarm sensor
- ✓ Switch on button / Key tones adjustment
- ✓ High vision LCD display / Backlit display screen / Eight level of contrast
- ✓ Six language menu (IT, EN, FR, DE, ES, GR)
- ✓ Able to control free fall windlasses
- ✓ Parallel connection
- ✓ USB cable included
- ✓ Support bracket for stowing

Code	73633
Command Transmission	Remote
Number of Buttons	3 (Transmitter)
Voltage (V DC)	12 - 24 (Receiver)
Operating Temperature (°C)	From -10 to +60
Protection Rating*	IP66 (Transmitter)
Max. Contacts Amperage (A)	2 (Receiver)
Weight (g)**	140 (Transmitter) 110 (Receiver)
Dimensions (mm)	155 x 65 x 45 (Transmitter) 69 x 133 x 30 (Receiver)

\*When installed \*\*With fixing lugs